

Tilspænding + ventilspillerum gængse Kubota modeller

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
Super Mini E2B / Tier 2	Z482 , Z 602 D722 , D 902	M8x1,25 39,2-44,1 Nm	M7x0,75 26,5-30,4 Nm	Ind + Ud (kold) 0,145-0,185 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
Super Mini EB / Tier1	Z482 , Z602 D722 , D 902	M8x1,25 37,3-42,2 Nm	M7x0,75 26,5-30,4 Nm	Ind + Ud (kold) 0,145-0,185 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
05- Serien E3B / Tier3	D1005 , D 1105 + T D1305 , V 1505 + T	M10x1,25 64,0-68,0 Nm	M8x1,00 42,0-46,0 Nm	Ind + Ud (kold) 0,145-0,185 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
05- Serien E2B / Tier2 EB / Tier1	D905, D1005 D1105 + T V1505 + T	M10x1,25 63,7-68,6 Nm	M8x1,00 41,2-46,1 Nm	Ind + Ud (kold) 0,145-0,185 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
03M- Serien Interim E3B / Tier4	D1503M, D1703M + BG V2003M, V2203M + BG V2403M + DI + T	M11x1,25 93,2-98,0 Nm	M8x1,00 Gl.type: 45,0-49,0 Nm Ny type: 41,0-45,0 Nm	Ind + Ud (kold) 0,18-0,22 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
03M- Serien E2B / Tier2	D1503M, D1703M V2003M + T V2203M, V2403M	M11x1,25 93,2-98,0 Nm	M8x1,00 Gl.type: 45,0-49,0 Nm Ny type: 41,0-45,0 Nm	Ind + Ud (kold) 0,145-0,185 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
03- Serien E2B / Tier2	D1403 ,D 1503, D 1703 V1903, V2003-T, V 2203	M11x1,25 93,2-98,0 Nm	M8x1,00 Gl.type: 45,0-49,0 Nm Ny type: 41,0-45,0 Nm	Ind + Ud (kold) 0,18-0,22 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
V 3-Serien E3B / Tier3 Interim Tier4	V3300 BG, V3600 + T V3600-T + BG V3800DI-T + BG	M12x1,25 98,1-107,9 Nm	M10x1,25 78,5-83,4 Nm	Ind + Ud (kold) 0,23-0,27 mm

Emissionstrin	Motortype	Topbolt	Plejlbolt	Ventilspil
V3- Serien E2B/Tier 1+2	V3300, V3300-T V3800DI, V3800DI-T	M12x1,25 98,1-107,9 Nm	M10x1,25 78,5-83,4 Nm	Ind + Ud (kold) 0,23-0,27 mm